

種類	型式		吸上高さ(m) ←						→ 押上高さ(m)			銘板表示給水量(L/分)	同時使用水栓数の目安(個)
	ジェット型式	井戸深さ	30	20	10	0	10	20	30	0	50		
浅井戸用自動ポンプ	WT-P125W		8		14						22	28	2~3
	WT-P200W・WT-K200W		8		18				26		28	35	3~4
	WT-P300W		7		18				26		33	39	3~4
	WT-P400W		8		23				30		42		4
	WT-K750W		7		23				30		64		6
浅井戸・加圧給水用自動フラタ式ポンプ	WM-P150X		8		17					22	28	2~3	
	WM-P250X		8		23				29	28	35	3~4	
	WM-P400X		8		26				32	42	46	4~5	
	WM-K750X		8		26				32	51	70	5~7	
浅深両用自動ポンプ	CT-P150W	J15-6W	浅井戸の時	6		10					24	2	
			深井戸の時	12		10					15.5	1~2	
	CT-P250W	J25-6W	浅井戸の時	6		15					37	3~4	
			深井戸の時	12		15					28	3	
	CT-K250W	J25-24W	18mの時	18		15					18	2	
			24mの時	24		15					11	1	
	CT-P400W	J40-6W	浅井戸の時	6		16					50	5	
			深井戸の時	12		16					38	3~4	
		J75-24W	18mの時	18		16					26	2~3	
	24mの時		24		16					17	1~2		
	30mの時		30		16					11	1		
	CT-P600W	J40-6W	浅井戸の時	6		16					55	5~6	
			深井戸の時	12		16					46	4~5	
		J75-24W	18mの時	18		16					32	3	
			24mの時	24		16					22	2	
		J75-35W	30mの時	30		16					14	1~2	
	35mの時	35		16						10	1		
	CT-K750W	J75-6W	浅井戸の時	6		16					62	6	
			深井戸の時	12		16					50	5	
		J75-24W	18mの時	18		16					37	3~4	
24mの時			24		16					25	2~3		
J75-35W		30mの時	30		16					17	2		
35mの時	35		16						12	1			
DM-P400W	J75-24W	12mの時	12		16					38	3~4		
		18mの時	18		16					28	3		
	J75-35W	24mの時	24		16					17	1~2		
		30mの時	30		16					12	1		
	DM-P600W	J75-24W	12mの時	12		16					39	3~4	
			18mの時	18		16					29	3	
		24mの時	24		16					18	2		
		J75-35W	30mの時	30		16					13	1	
35mの時			35		16					8	1		
DM-K750W	J75-24W	12mの時	12		16					40	4		
		18mの時	18		16					32	3		
		24mの時	24		16					19	2		
	J75-35W	30mの時	30		16					14	1~2		
		35mの時	35		16					10	1		
SFM-P450W			30		15					32(50Hz)	39(60Hz)	4	
			40		15					26(50Hz)	30(60Hz)	3	
			42		15					39(50Hz)	41(60Hz)	4	